

Emulsion Analysis Report

Ergon Asphalt and Emulsions

14929 Slover Ave. Fontana, CA. 92337
(909)829-0505 Fax (909)829-8074

Consigned To: Diversified Asphalt

Product: SS-1H

Tank No. 19

THIS CERTIFICATION OF COMPLIANCE IS TO ASSURE THAT THE MATERIAL AS DESCRIBED CONFORMS TO APPROPRIATE STATE AND FEDERAL SPECIFICATIONS (AASHTO M 140-3, CALTRANS SPECIFICATIONS: SECTION 94, ASTM: D 977-05). OUR CURRENT TYPICAL PROPERTIES ARE AS FOLLOWS:

TEST RESULTS

Test on Emulsion	Specification
Viscosity SSF @ 77 F.	35.8 20-100
Residue by Evaporation	62.10 % Min. 57
Oil by Evaporation	%
Water Content	37.90 %
Storage Stability Test 24hr	0.07 % Max. 1.0
Settlement 5 days	0.51 % Max. 5.0
Demulsibility	%
Sieve Test	0.02 % Max. .1
Cement Mix	0.04 % Max. 2.0

Test On Residue From Evaporation

Pen @ 77 F, 100g 5sec	66 40-90
Float Test	sec.
Softening Point (R&B)	
Ductility @ 77 F 5 cm/min	91 cm/Min. 40
Specific Gravity @ 60 F	
Solubility	98.1 Min. 97.5
Ash	
Torsional Recovery	

We hereby certify that the above determinations were performed in accordance with the specified test methods and that the product designated conforms to the specifications for the indicated grade.

Tested By: Sabrina Perez

Date: 6/2/2009