



Marathon Petroleum Company LP

1201 China Grade Loop
Bakersfield, CA 93308

PRODUCT: HPS (No Track Tack)

CODE No: 13828

DATE: 4/1/2021

TANK No.:

Purchaser:

Destination:

Transporter:

Truck & Trailer No.:

Bill of Lading No.:

Contract No.:

Job No.:

Purchase Order No.:

Quantity, Lbs.:

Meets Specifications: ASTM D 6373 Mod.; AASHTO M 320 Mod.; Caltrans Section 92; AGC Greenbook Section 203-1.

CERTIFICATE OF COMPLIANCE/ ANALYSIS

TESTS	ASTM	AASHTO	SPECIFICATION	RESULT
Tests on Original Asphalt:				
Viscosity, 135°C, 21 Spindle, 20 RPM, Pa·s	D-4402	T-316	3.0 max	1359.000
Viscosity, 165°C, 21 Spindle, 20 RPM, Pa·s	D-4402	T-316	.3 max	0.288
Flash Point, C.O.C., °C	D 92	T- 48	230 min	305
Softening Point, °C	D-36	T-53	71°C min	84
Penetration @ 25°C	D-5	T-49	6-18 dmm	9
Solubility in Trichloroethylene, wt. %	D-2042	T-44	97.5 min	99.4

We hereby certify that the above material was sampled, tested and complies with all applicable standards & specifications

This certification is valid for up to 30 days from the day of issue

Material temperature is less than 375 degrees Fahrenheit or at least 25 degrees Fahrenheit below the product's flash point.



Certified By:

Name:

Title:

Kevin McKinney

Technical Lead, Specialty Products