## SAFETY DATA SHEET

#### 1. Identification

**Product identifier** 

**Deery Hot Applied Sealants** 

Other means of identification

Not available.

Synonym(s)

101, 101ELT, 101ELTCH, 101KS, 101MI, 102, 102GL,102GL-18B, 102P, 102PL, 103, 103-25, 103-25103GL, 103GLCA, 103GLCH, 103GLWY, 103P, 110, 115, 115AR, 115UT, 180, 180CA, 180NE, 200, 200CA, 200MC, 210, 220, 220CA, 6690-III, 974, 974D, 3723, 3723CH, 5078, 5078-GA-M, 5078PMAR, 5078CO, 5078TXA, 5078TXB, Type 3 Asphalt, PLS, PRO-PL, PLF 210, Modified AC & Fiber, Asphalt & Fiber, Cold Joint Adhesive, Loop Sealant LW, Loop Sealant P650, PLS, SAMA,

SUPER STRETCH, Pro PL, Sunflex, Membrane #6, Asphalt Cement

Recommended use

Pavement Crack and Joint Sealing and Preservation

**Recommended restrictions** 

None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Manufacturer:

Crafco, Inc.

420 Roosevelt Avenue

Chandler, AZ 85226 USA

**Contact Name:** 

Address:

Jim Chehovits

Telephone: E-mail:

1-800-227-4059

**CHEMTREC:** 

jim.chehovits@crafco.com

800-424-9300

# 2. Hazard(s) identification

**Physical hazards** 

Not classified.

**Health hazards** 

Not classified.

**Environmental hazards** 

Not classified.

**OSHA** defined hazards

Not classified.

\*Hazards not stated here are "Not classified", "Not applicable" or "Classification not possible".

#### Label elements

**Hazard** symbol

None.

Signal word

None.

**Hazard statement** 

Not applicable.

Prevention

Wear suitable eye/face protection.

Response

Specific treatment see Section 4 of this SDS.

Storage Disposal

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%	
ASPHALT		8052-42-4	20 - 100	
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC		64742-52-5	0 - 40	
Other components below reportable lev	els	*	0 - 75	

## 4. First-aid measures

Inhalation

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention, if needed. Call a physician if symptoms develop or persist.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Material name: Deery Hot Applied Sealants

SDS US 5596 Version #: 02 Revision date: 09-18-2014 Issue date: 01-07-2014

Skin contact

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Thoroughly wash (or discard) clothing and shoes

before reuse

Not available.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Get medical attention if irritation develops and

persists.

Ingestion

Rinse mouth. Do not induce vomiting. Do not use mouth-to-mouth method if victim ingested the

substance. Call a POISON CENTER or doctor/physician if you feel unwell.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

**General information** 

In case of ingestion, the decision of whether or not to induce vomiting should be made by the attending physician. Certain pre-existing conditions may make workers particularly susceptible to the effects of this chemical: asthma, allergies, impaired pulmonary function.

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Discard any shoes or clothing items that cannot be decontaminated.

# 5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Addition of water or foam to the fire may cause frothing.

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters Fire may produce irritating, corrosive and/or toxic gases. Development of hazardous combustion gases or vapours possible in the event of a fire. The following may develop: Acrolein.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear full protective clothing including self contained breathing apparatus. Structural firefighters protective clothing will only provide limited protection.

Fire-fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. In the event of fire, cool tanks with water spray. By fire, toxic gases may be formed (COx, NOx). Keep run-off water out of sewers and water sources. Dike for water control.

Specific methods

In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Ventilate closed spaces before entering them. Do not touch or walk through spilled material.

Methods and materials for containment and cleaning up

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Dike far ahead of spill for later disposal. Following product recovery, flush area with water.

Never return spills in original containers for re-use.

**Environmental precautions** 

Prevent further leakage or spillage if safe to do so. Runoff or release to sewer, waterway or ground is forbidden.

## 7. Handling and storage

Precautions for safe handling

The product is non-combustible. If heated, irritating vapors may be formed. Do not use in areas without adequate ventilation. Wash hands thoroughly after handling. Wash hands after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a well-ventilated place. Keep the container tightly closed and dry. Store in a closed container away from incompatible materials. Keep out of the reach of children.

## 8. Exposure controls/personal protection

#### Occupational exposure limits

US. OSHA Table Z-1	<b>Limits for Air Contaminants</b>	(29 CFR 1910.1000)
· · · · · · · · · · · · · · · · · · ·		(

Components Value **Form** Type **DISTILLATES** PEL 5 mg/m3 Mist. (PETROLEUM),

HYDROTREATED HEAVY NAPHTHENIC (CAS

64742-52-5) **US. ACGIH Threshold Limit Values** 

Components Value **Form** Type ASPHALT (CAS 8052-42-4) TWA 0.5 mg/m3 Inhalable fraction.

**US. NIOSH: Pocket Guide to Chemical Hazards** Components Value **Form** Type ASPHALT (CAS 8052-42-4) Ceiling 5 ma/m3 Fume. DISTILLATES STEL 10 mg/m3 Mist. (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)

**Biological limit values** No biological exposure limits noted for the ingredient(s).

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined Appropriate engineering

controls occupational exposure limit is not exceeded. Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses; chemical goggles (if splashing is possible). Wear chemical goggles; face shield

(if handling molten material).

TWA

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

Other Wear suitable protective clothing and eye/face protection. Use of an impervious apron is

recommended.

Skin protection

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards During product use, there is a risk of thermal burns.

**General hygiene** considerations

When using do not smoke. Avoid contact with eyes. Avoid contact with skin. Keep away from food

Mist.

5 mg/m3

and drink. Handle in accordance with good industrial hygiene and safety practice.

## 9. Physical and chemical properties

**Appearance** Solid **Physical state** Solid. Form Solid.

> Color Black, Dark brown

Product is a black, semi-solid with a burnt tar odor. Odor

**Odor threshold** Not available. Not available.

150 - 250 °F (65.56 - 121.11 °C) ASTM D36 Softening Point Melting point/freezing point

Initial boiling point and

> 800 °F (> 426.67 °C) boiling range

Flash point > 400.0 °F (> 204.4 °C)

**Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit -Not available.

upper (%)

Material name: Deery Hot Applied Sealants

5596 Version #: 02 Revision date: 09-18-2014 Issue date: 01-07-2014

Explosive limit - lower

(%)

Explosive limit - upper

Not available.

Not available.

(%)

Vapor pressure Vapor density

Not available. Not available.

Relative density

Not available.

Solubility(ies)

Solubility (water) Partition coefficient (n-octanol/water)

Not available. Not available.

Auto-ignition temperature

> 700 °F (> 371.11 °C)

**Decomposition temperature** 

Not available.

Viscosity

Not available.

Other information

**Density** 

Not Available

Flammability class

Combustible IIIB estimated

Percent volatile

0 %

Specific gravity 1 - 1.9

## 10. Stability and reactivity

Reactivity

Not available.

Chemical stability

Conditions to avoid

Material is stable under normal conditions. Hazardous polymerization does not occur.

Possibility of hazardous

reactions

Strong oxidizing agents.

**Incompatible materials** 

Incompatible with oxidizing agents.

Hazardous decomposition

Upon decomposition, product emits acrid dense smoke with carbon dioxide, carbon monoxide, trace oxides of nitrogen and sulfur, and water.

products

## 11. Toxicological information

## Information on likely routes of exposure

Ingestion

May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Inhalation

May cause irritation to the respiratory system.

Skin contact

Irritating to skin.

Eve contact

Causes eve irritation. Molten material will produce thermal burns.

Symptoms related to the

physical, chemical and toxicological characteristics Not available.

## Information on toxicological effects

**Acute toxicity** 

Not available.

Skin corrosion/irritation

Defats the skin. Causes irritation.

Serious eye damage/eye

irritation

Irritating to eyes.

## Respiratory or skin sensitization

Respiratory sensitization

Not available.

Skin sensitization

Irritating to skin.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

## IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4)

2B Possibly carcinogenic to humans.

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity

Contains no ingredient listed as toxic to reproduction

Material name: Deery Hot Applied Sealants

SDS US 5596 Version #: 02 Revision date: 09-18-2014 Issue date: 01-07-2014 4/7

Specific target organ toxicity

- single exposure

Not available.

Specific target organ toxicity

- repeated exposure

Not available.

Aspiration hazard

Not available.

**Chronic effects** 

Prolonged inhalation may be harmful. May cause eczema-like skin disorders (dermatitis).

# 12. Ecological information

**Ecotoxicity** 

This product has no known eco-toxicological effects. Not expected to be harmful to aquatic

organisms.

Persistence and degradability

Not available.

Bioaccumulative potential Mobility in soil

Not available.

Other adverse effects

Not available.

# 13. Disposal considerations

**Disposal instructions** 

Dispose of contents/container in accordance with local/regional/national/international regulations. When this product as supplied is to be discarded as waste, it does not meet the definition of a

RCRA waste under 40 CFR 261.

Hazardous waste code

Not applicable.

Waste from residues / unused products

Dispose of in accordance with local regulations.

Contaminated packaging

Offer rinsed packaging material to local recycling facilities.

## 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

Further information

If the product is shipped at ambient temperature, not regulated for transport by ground, air or vessel. If shipped above 212 deg F: "UN3257, Elevated Temperature Liquid, n.o.s. (Asphalt

mixture), 9, PG III"

## 15. Regulatory information

**US federal regulations** 

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

**ASPHALT (CAS 8052-42-4)** 

Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Hazard categories** 

Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312

No

Hazardous chemical

SARA 313 (TRI reporting)

Not regulated.

Material name: Deery Hot Applied Sealants

5596 Version #: 02 Revision date: 09-18-2014 Issue date: 01-07-2014

SDS US

#### Other federal regulations

## Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

**US state regulations** 

WARNING: This product contains a chemical known to the State of California to cause cancer.

## US. Massachusetts RTK - Substance List

ASPHALT (CAS 8052-42-4)

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)

## US. New Jersey Worker and Community Right-to-Know Act

Not regulated.

## US. Pennsylvania RTK - Hazardous Substances

ASPHALT (CAS 8052-42-4)

## **US. Rhode Island RTK**

Not regulated.

## **US. California Proposition 65**

## US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT (CAS 8052-42-4)

Listed: January 1, 1990

## **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*	
Australia	Australian Inventory of Chemical Substances (AICS)	•	Yes
Canada	Domestic Substances List (DSL)		Yes
Canada	Non-Domestic Substances List (NDSL)		No
China	Inventory of Existing Chemical Substances in China (IECSC)		Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	·	Yes
Europe	European List of Notified Chemical Substances (ELINCS)		No
Japan	Inventory of Existing and New Chemical Substances (ENCS)		Yes
Korea	Existing Chemicals List (ECL)		Yes
New Zealand	New Zealand Inventory		Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)		Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory		Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

## 16. Other information, including date of preparation or last revision

 Issue date
 01-07-2014

 Revision date
 09-18-2014

 Version #
 02

Further information HMIS® is a registered trade and service mark of the NPCA.

Material name: Deery Hot Applied Sealants

5596 Version #: 02 Revision date: 09-18-2014 Issue date: 01-07-2014

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### References

**ACGIH** 

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

Korea. Accidental Release Prevention Substances (Presidential Decree of Toxic Chemical Control Law, Executive Order No. 19203)

Korea. Dangerous Substances Threshold Quantity (Presidential Decree of Dangerous Substances Safety Management Act No. 18406, Schedule 1)

Korea. Harmful Substances Prohibited from Manufacturing (Presidential Decree on the Industrial Safety and Health Act (No. 13053), Article 29)

Korea. Harmful Substances Requiring Permission for Manufacture or Use (Presidential Decree on the Industrial Safety and Health Act (No. 13053), Article 30)

Korea. Non-Toxic Chemicals List (National Institute of Environment Research (NIER) Public Notice No. 1997-10, as amended)

Korea, Observational Chemicals (Ministerial Decree of TCCL Article 6)

Korea. OELs. Regulation for Permitted Concentration of Hazardous Substances (Ministry of Labor (MOL) Public Notice No. 1986-45, as amended)

Korea. Prohibited Chemical Substances (TCCL Article 11)

Korea. Regulated volatile organic compounds (VOCs) (MOE Notice No. 2001-36, March 8, 2001, as amended)

Korea. Restricted Chemical Substances (TCCL Article 11)

Korea. Toxic Chemical Control Law (TCCL), Existing Chemicals Inventory (KECI)

Korea. Toxic Chemical Control Law (TCCL), pre-1997 List

Korea, Toxic Chemicals (TCCL Article 10)

Korea. Toxic Release Inventory (TRI) Chemicals (TCCL Article 14)

Taiwan. Dangerous Materials (Rules on Hazard Communication of Dangerous Materials and Toxic Materials)

Taiwan. Industrial Precursor Chemicals (Categories and Regulations Governing Inspection and Declaration of Industrial Precursor Chemicals, MOEA Decree No. 87, as amended)

Taiwan. OELs. (Standards on Workplace Atmosphere of Dangerous and Hazardous Materials) Taiwan. Toxic Chemical Substances (TCS) (List of Toxic Chemical Substances announced by the Environmental Protection Administration)

Taiwan. Toxic Materials (Rules on Hazard Communication of Dangerous Materials and Toxic Materials)

HSDB® - Hazardous Substances Data Bank

JIS Z 7250: 2005 Safety data sheet for chemical products-Part 1:Content and order of sections JCIA GHS Guideline, October 2008

IARC Monographs. Overall Evaluation of Carcinogenicity
National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices
Japan Society for Occupational Health, Recommendation of Occupational Exposure Limits

The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

#### **Revision Information**

Disclaimer

Hazard(s) identification: GHS Symbols

Composition/information on ingredients: Composition comments

**GHS: Classification** 

